

### [54] PRESSURE-SENSITIVE TABLET

[75] Inventors: Takashi Taniguchi, Yaso; Shoichi Kurasaki, Kouga; Koichiro Oka, Ibaraki, all of Japan

[73] Assignee: Toray Industries, Inc., Tokyo, Japan

[21] Appl. No.: 214,438

[22] Filed: Jul. 1, 1988

### [30] Foreign Application Priority Data

Jul. 3, 1987 [JP] Japan ..... 62-167388  
Nov. 5, 1987 [JP] Japan ..... 62-280105  
Feb. 24, 1988 [JP] Japan ..... 63-43083

[51] Int. Cl.<sup>5</sup> ..... B32B 5/16; G08C 21/00

[52] U.S. Cl. .... 428/327; 178/18;  
428/323

[58] Field of Search ..... 178/18, 19, 20;  
428/327; 340/706

### [56] References Cited

#### U.S. PATENT DOCUMENTS

3,911,215 10/1975 Hurst et al. .... 178/18  
4,220,815 9/1980 Gibson et al. .... 178/18  
4,707,570 11/1987 Ide et al. .... 178/18

*Primary Examiner*—George F. Lesmes

*Assistant Examiner*—Christopher Brown

*Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch

### [57] ABSTRACT

A pressure-sensitive tablet having desired sensitivity, excellent durability, and a good appearance. The pressure-sensitive tablet comprises an electro-conductive substrate; deformable insulative particles with an average diameter of 0.1  $\mu$ m to 100  $\mu$ m, which are distributed on the substrate and an electron-conductive film superimposed on the deformable particles.

18 Claims, 2 Drawing Sheets

